



## TRAVI HEB

### S275JR/S355J2

TRAVI HEB	BASE	ALTEZZA	SP.ASTA	SP.ALI	KG. / ML.
100	100	100	6,0	11,0	20,4
120	120	120	6,5	11,0	26,7
140	140	140	7,0	12,0	33,7
160	160	160	8,5	14,0	42,6
180	180	180	9,0	14,0	51,2
200	200	200	9,5	16,0	61,3
220	220	220	10,0	16,0	71,5
240	240	240	10,0	18,0	83,2
260	260	260	10,5	18,0	93,0
280	280	280	11,0	20,0	103,0
300	300	300	11,5	20,0	117,0
320	320	300	12,0	20,5	127,0
360	360	300	12,5	22,5	142,0

**DISPONIBILI LUNGHEZZE 6000 & 12000 mm**  
**POSSIBILITA' DI TAGLIO A MISURA**

## TABELLE PORTATE E SOLLECITAZIONI

<b>PORTATA HEA SOLL. A FLESSIONE IN Q.LI</b>										
<b>DISTANZA TRA GLI APPOGGI IN METRI</b>										
	3	4	5	6	7	8	9	10	11	12
100	38	28	22	18	15					
120	60	45	35	29	24	21				
140	91	68	53	44	37	32	27			
160	131	98	77	64	54	46	40	35		
180	180	134	106	88	74	64	55	49	44	
200	241	180	143	118	100	86	75	67	59	53
220	312	232	185	153	129	112	98	87	78	70
240	398	297	236	195	166	143	126	112	100	90
260	488	364	290	240	204	176	155	138	123	111
280	586	437	348	228	245	212	187	166	149	135
300	713	533	424	351	299	259	228	203	182	165
320	820	612	488	404	344	299	263	234	210	190
360	1020	761	607	503	429	372	328	293	263	239

<b>PORTATA HEB SOLL. A COMPRESSIONE IN Q.LI</b>										
<b>ALTEZZA DEI PILASTRI IN METRI</b>										
	3	3,5	4	4,5	5	5,5	6	6,5	7	8
100	228	198	170	138	113	93	78			
120	340	307	273	243	215	178	150	127		
140	468	433	395	358	323	290	261	221	190	
160	616	579	543	499	464	422	384	352	308	
180	774	736	697	653	611	568	525	481	446	359
200	961	919	873	827	781	735	686	641	595	518
220	1137	1095	1055	1011	958	910	861	818	759	671
240	1346	1305	1246	1203	1161	1116	1060	1003	953	852
260	1528	1480	1424	1393	1343	1289	1238	1184	1121	1024
280	1723	1668	1617	1581	1524	1480	1430	1374	1314	1201
300	1971	1924	1864	1821	1767	1716	1668	1601	1549	1428
320	2133	2081	2016	1970	1912	1857	1793	1732	1676	1545
360	2350	2311	2257	2206	2125	2079	2006	1926	1876	1710

