



TRAVI HEM

S275JR/S355J2

TRAVI HEM	BASE	ALTEZZA	SP.ASTA	SP. ALI	KG. / ML.
100	106	120	12,0	20,0	41,8
120	126	140	12,5	21,0	52,1
140	142	160	13,0	22,0	63,2
160	166	180	14,0	23,0	76,2
180	186	200	14,5	24,0	88,9
200	206	220	15,0	25,0	103,0

DISPONIBILI LUNGHEZZE 6000 & 12000 mm
POSSIBILITA' DI TAGLIO A MISURA

TABELLE PORTATE E SOLLECITAZIONI

PORTATA HEM SOLLECITATE A FLESSIONE IN Q.LI										
DISTANZA TRA GLI APPOGGI IN METRI										
	3	4	5	6	7	8	9	10	11	12
100	80	59	40	38	32	27				
120	121	90	71	58	49	42	36			
140	173	129	102	84	71	61	53	46		
160	239	178	141	116	98	84	73	65	57	
180	316	236	187	154	130	112	98	87	77	69
200	409	305	242	200	170	146	128	113	101	90

PORTATA HEM SOLL. A COMPRESSIONE IN Q.LI										
ALTEZZA DEI PILASTRI IN METRI										
	3	3,5	4	4,5	5	5,5	6	6,5	7	8
100	498	441	383	334	268	221	189			
120	690	629	568	506	448	345	331	281		
140	895	873	772	701	641	581	526	457	395	
160	1134	1064	1002	930	858	797	722	664	609	
180	1363	1304	1233	1169	1092	1018	944	880	809	687
200	1616	1545	1490	1410	1356	1265	1187	1123	1045	909